



Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 10/15/2015

ADVANTAGE®

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Heavy Duty Oven & Grill- 6322, 6324, 6326
Product code : 20116

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Advantage Chemical, LLC
Temecula, CA, 92590
T 1-855-238-2436

1.4. Emergency telephone number

Emergency number : 1-800-424-9300
ChemTrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Met. Corr. 1 H290
Skin Corr. 1A H314
Eye Dam. 1 H318

Full text of H-statements: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H290 - May be corrosive to metals
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage

Precautionary statements (GHS-US) : P234 - Keep only in original container
P260 - Do not breathe dust/fume/gas/mist/vapours/spray
P264 - Wash hands, forearms and face thoroughly after handling
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P363 - Wash contaminated clothing before reuse
P390 - Absorb spillage to prevent material damage
P405 - Store locked up
P406 - Store in Original container or corrosive resistant container with a resistant inner liner
P501 - Dispose of contents/container to a licensed hazardous waste facility in accordance with state and local agencies

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

Not applicable

Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
sodium hydroxide, conc=50%, aqueous solution	(CAS No) 1310-73-2	5 - 25	Skin Corr. 1A, H314
disodium metasilicate	(CAS No) 6834-92-0	1 - 10	Skin Corr. 1A, H314
potassium hydroxide, conc=50%, aqueous solution	(CAS No) 1310-58-3	1 - 10	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Aquatic Acute 3, H402
2-aminoethanol	(CAS No) 141-43-5	1 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314
2-butoxyethanol	(CAS No) 111-76-2	1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.
Explosion hazard : May form flammable/explosive vapour-air mixture.
Reactivity : Thermal decomposition generates : Corrosive vapours.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Absorb spillage to prevent material damage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : May be corrosive to metals.
Precautions for safe handling : Avoid contact with skin, eyes and clothing.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.
Storage conditions : Keep only in original container in a cool well ventilated area. Keep container closed when not in use.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
Storage temperature : 25 (5 - 42) °C
Packaging materials : polyethylene. Do not store in corrodable metal.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Heavy Duty Oven & Grill- 6322, 6324, 6326		
ACGIH	Not applicable	
OSHA	Not applicable	
2-butoxyethanol (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
OSHA	Not applicable	
disodium metasilicate (6834-92-0)		
ACGIH	Not applicable	
OSHA	Not applicable	
potassium hydroxide, conc=50%, aqueous solution (1310-58-3)		
ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
OSHA	Not applicable	
2-aminoethanol (141-43-5)		
ACGIH	ACGIH TWA (ppm)	3 ppm
ACGIH	ACGIH STEL (ppm)	3 ppm
OSHA	Not applicable	
sodium hydroxide, conc=50%, aqueous solution (1310-73-2)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye protection	: Chemical goggles or face shield.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown
Odour	: characteristic
Odour threshold	: No data available
pH	: 13 (12.5 - 14)
Melting point	: No data available
Freezing point	: <= 0 °C
Boiling point	: >= 100 °C
Flash point	: None
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20 °C	: No data available
Density	: >= 1.12 (1.11 - 1.13) g/ml
Solubility	: Soluble in water. Water: Solubility in water of component(s) of the mixture : • 2-butoxyethanol: Complete • tetrasodium ethylenediaminetetracetate: 103 g/100ml • disodium metasilicate: > 18 g/100ml • potassium hydroxide, conc=50%, aqueous solution: 121 g/100ml (25 °C) • 2-aminoethanol: Complete • sodium hydroxide, conc=50%, aqueous solution: Complete
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

VOC content	: <= 32.4
-------------	-----------

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates : Corrosive vapours.

10.2. Chemical stability

No additional information available

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases. metals. May be corrosive to metals.

Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases. Thermal decomposition generates : Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

2-butoxyethanol (111-76-2)	
LD50 oral rat	530 mg/kg (1746 mg/kg bodyweight; Rat; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Experimental value,Rat; Experimental value)
LD50 dermal rabbit	435 mg/kg bodyweight (435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value,435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (2.35 mg/l/4h; Rat; Rat; Experimental value; Experimental value,2.35 mg/l/4h; Rat; Rat; Experimental value; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat
ATE US (oral)	530.000 mg/kg bodyweight
ATE US (dermal)	435.000 mg/kg bodyweight
ATE US (vapours)	2.170 mg/l/4h
ATE US (dust,mist)	2.170 mg/l/4h

disodium metasilicate (6834-92-0)	
LD50 dermal rat	> 5000 mg/kg bodyweight (Rat; Read-across; OECD 402: Acute Dermal Toxicity)

potassium hydroxide, conc=50%, aqueous solution (1310-58-3)	
LD50 oral rat	333 mg/kg (Rat)
ATE US (oral)	333.000 mg/kg bodyweight

2-aminoethanol (141-43-5)	
LD50 oral rat	1720 mg/kg (Rat)
LD50 dermal rabbit	1018 mg/kg (Rabbit)
ATE US (oral)	1720.000 mg/kg bodyweight
ATE US (dermal)	1018.000 mg/kg bodyweight

Skin corrosion/irritation : Causes severe skin burns and eye damage.

pH: 13 (12.5 - 14)

Serious eye damage/irritation : Causes serious eye damage.

pH: 13 (12.5 - 14)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

2-butoxyethanol (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

2-butoxyethanol (111-76-2)	
LC50 fish 1	116 ppm (96 h; Cyprinodon variegatus; Nominal concentration)

Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-butoxyethanol (111-76-2)	
EC50 Daphnia 1	1700 mg/l (48 h; Daphnia sp.; Nominal concentration)
LC50 fish 2	1341 ppm (96 h; Lepomis macrochirus)
EC50 Daphnia 2	1720 mg/l (24 h; Daphnia magna)
TLM fish 1	100 - 1000,96 h; Pisces
TLM other aquatic organisms 1	100 - 1000,96 h
Threshold limit algae 1	900 mg/l (168 h; Scenedesmus quadricauda)
Threshold limit algae 2	35 mg/l (192 h; Microcystis aeruginosa)
disodium metasilicate (6834-92-0)	
LC50 fish 1	210 mg/l (96 h; Brachydanio rerio)
EC50 Daphnia 1	216 mg/l (96 h; Daphnia magna; GLP)
LC50 fish 2	2320 mg/l (96 h; Gambusia affinis)
EC50 Daphnia 2	632 mg/l (96 h; Lymnaea sp.)
Threshold limit algae 1	207 mg/l (72 h; Scenedesmus subspicatus; GLP)
potassium hydroxide, conc=50%, aqueous solution (1310-58-3)	
LC50 fish 1	28.6 mg/l (24 h; Pisces; Pure substance)
LC50 other aquatic organisms 1	100 - 1000 mg/l (96 h)
LC50 fish 2	80 mg/l (96 h; Gambusia affinis; Pure substance)
Threshold limit other aquatic organisms 1	100 - 1000,96 h
2-aminoethanol (141-43-5)	
LC50 fish 1	150 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	140 mg/l (24 h; Daphnia magna)
LC50 fish 2	329.16 mg/l (96 h; Lepomis macrochirus)
TLM fish 1	100 - 1000,96 h; Pisces
TLM other aquatic organisms 1	100 - 1000,96 h
Threshold limit algae 1	0.97 mg/l (192 h; Scenedesmus quadricauda; Inhibitory)
Threshold limit algae 2	35 mg/l (72 h; Algae)

12.2. Persistence and degradability

Heavy Duty Oven & Grill- 6322, 6324, 6326	
Persistence and degradability	Not established.
2-butoxyethanol (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.20 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31 % ThOD
disodium metasilicate (6834-92-0)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
potassium hydroxide, conc=50%, aqueous solution (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
2-aminoethanol (141-43-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.

Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-aminoethanol (141-43-5)	
Biochemical oxygen demand (BOD)	0.80 g O ₂ /g substance
Chemical oxygen demand (COD)	1.34 g O ₂ /g substance
ThOD	2.49 g O ₂ /g substance
BOD (% of ThOD)	0.32 % ThOD

sodium hydroxide, conc=50%, aqueous solution (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the components available.

12.3. Bioaccumulative potential

Heavy Duty Oven & Grill- 6322, 6324, 6326	
Bioaccumulative potential	Not established.

2-butoxyethanol (111-76-2)	
Log Pow	0.81 (Experimental value; 25 °C, Experimental value; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

disodium metasilicate (6834-92-0)	
Bioaccumulative potential	Bioaccumulation: not applicable.

potassium hydroxide, conc=50%, aqueous solution (1310-58-3)	
Bioaccumulative potential	Bioaccumulation: not applicable.

2-aminoethanol (141-43-5)	
Log Pow	-1.91
Bioaccumulative potential	Bioaccumulation: not applicable.

sodium hydroxide, conc=50%, aqueous solution (1310-73-2)	
Bioaccumulative potential	Does not contain bioaccumulative component(s).

12.4. Mobility in soil

2-butoxyethanol (111-76-2)	
Surface tension	0.027 N/m (25 °C)

2-aminoethanol (141-43-5)	
Surface tension	0.050 N/m

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/containers in hazardous or special waste collection point, an approved disposal plant, a licensed hazardous waste disposal contractor or authorized waste collection site in accordance with local, regional and/or international regulation, except for empty clean containers which can be disposed of as non hazardous waste.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s., 8, II

UN-No.(DOT) : UN1760

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: t_r is the maximum mean bulk temperature during transport, t_f is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (t_f) and the maximum mean bulk temperature during transportation (t_r) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d_{15} and d_{50} are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

2-butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 313 - Emission Reporting	100 % 2-butoxyethanol (N230 Certain Glycol Ethers)
---------------------------------------	--

disodium metasilicate (6834-92-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

potassium hydroxide, conc=50%, aqueous solution (1310-58-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
--	---------

2-aminoethanol (141-43-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

sodium hydroxide, conc=50%, aqueous solution (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Not subject to reporting requirements of the United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
--	---------

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

National regulations

No additional information available

15.3. US State regulations

2-butoxyethanol (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

potassium hydroxide, conc=50%, aqueous solution (1310-58-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

2-aminoethanol (141-43-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

sodium hydroxide, conc=50%, aqueous solution (1310-73-2)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 10/15/2015

Other information : None.

Heavy Duty Oven & Grill- 6322, 6324, 6326

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 3	Hazardous to the aquatic environment — Acute Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 4	Flammable liquids, Category 4
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H402	Harmful to aquatic life

NFPA health hazard

: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard


: 0 - Materials that will not burn.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

NFPA specific hazard

: None



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection

: C

C - Safety glasses, Gloves, Synthetic apron

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product