



**3M General Offices**  
3M Center  
St. Paul, MN 55144-1000  
1-800-364-3577 or (651) 737-6501 (24 hours)

2025-12-10 13:03:25.653

## Safety Data Sheet

---

Purchase Order #:  
Customer Number: 0026631593

SDS Coordinator  
VIELE & SONS INC  
1820 E VALENCIA DR  
FULLERTON, CA 92831-4847  
USA

Dear SDS Coordinator

Enclosed is the Safety Data Sheet (SDS)\* for the product that your company recently purchased from 3M.

The SDS being sent to you is required by the Supplier Notification Requirement of 40 CFR 372.45 (c 4), a part of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. The Supplier Notification Requirement requires the supplier to provide new notification to the recipient when the supplier changes an SDS in any of the following ways related to EPCRA Section 313 chemical(s):

- Additional EPCRA Section 313 chemical(s) were added to the SDS,
- The percent weight of any EPCRA Section 313 chemical(s) changed, or
- EPCRA 313 chemical(s) were deleted from the SDS.

Please forward the attached SDS to the individual in your organization responsible for implementing Title III of the Superfund Amendments and Reorganization Act of 1986 and 40 CFR Part 372 regulations.

This letter and accompanying SDS were created using a 3M computerized system. This system automatically prints and sends an SDS when a product is first ordered by a customer, when the SDS has been changed at the time of a subsequent order by the customer, or if renotification is warranted by Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 regulations.

3M SDSs are available over the Internet at [www.3m.com/MSDSSearch](http://www.3m.com/MSDSSearch).

3M is committed to meeting our customer requirements, and we ask that you contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

**If you are not currently receiving 3M SDSs by e-mail and would like to do so, please contact our eSDS Administrator at [emsdsadmin@mmm.com](mailto:emsdsadmin@mmm.com)**

\*An Article Information Sheet (AIS) or Article Information Letter (AIL) may be enclosed in place of an SDS if the product is an article which does not require an SDS under the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.



## Safety Data Sheet

Copyright,2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	10-2819-0	<b>Version Number:</b>	27.01
<b>Issue Date:</b>	12/10/25	<b>Supersedes Date:</b>	05/28/24

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Stainless Steel Cleaner & Polish

#### Product Identification Numbers

ID Number	UPC	ID Number	UPC
61-5000-6132-2	000-48011-14002-0	70-0713-1355-8	000-48011-59158-2
70-0713-1493-7	000-48011-59249-7		

7000000697, 7000011493, 7100134552, 7010340387

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Metal Polish, Cleans and polishes stainless steel, chrome, aluminum and laminated plastic surfaces.

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Commercial Branding and Transportation Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Aerosol Category 1

Specific Target Organ Toxicity (single exposure): Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Flame |Health Hazard |

**Pictograms****Hazard Statements**

Extremely flammable aerosol.

Pressurized container: may burst if heated.

Causes damage to organs: cardiovascular system.

**Precautionary statements****Prevention:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe vapor or spray.

Wash exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

**Response:**

IF exposed or concerned: Call a POISON CENTER or doctor.

Specific treatment (see Notes to Physician on this label).

**Storage:**

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).

**Disposal:**

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

**Notes to Physician:**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**Supplemental Information:**

Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	65 - 85
Mineral Oil	8042-47-5	10 - 30 Trade Secret *
Isobutane	75-28-5	7 - 13 Trade Secret *
Sorbitan Oleate	1338-43-8	0.5 - 1.5
Ethanolamine	141-43-5	< 0.5
Fragrance Compound	Trade Secret*	< 0.5

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. Get medical attention.

**Skin Contact:**

Wash with soap and water. If you feel unwell, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Target organ effects. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

**Substance**

Carbon monoxide

Carbon dioxide

**Condition**

During Combustion

During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

## 6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

## 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethanolamine	141-43-5	ACGIH	TWA:3 ppm;STEL:6 ppm	
Ethanolamine	141-43-5	OSHA	TWA:6 mg/m <sup>3</sup> (3 ppm)	
Butane, all isomers	75-28-5	ACGIH	STEL:1000 ppm	
Natural gas	75-28-5	ACGIH	Limit value not established:	simple asphyxiant
Mineral oil, excluding metal working fluids, pure, highly and severely refined, inhalable fraction	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m <sup>3</sup>	A4: Not class. as human carcin
OIL MIST (MINERAL)	8042-47-5	OSHA	TWA(as mist):5 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

### Skin/hand protection

No chemical protective gloves are required.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol
Color	White
Odor	Mild Citrus
Odor threshold	<i>No Data Available</i>
pH	9 - 11
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point/Initial boiling point/Boiling range	> 100 °C
Flash Point	No flash point
Evaporation rate	<i>No Data Available</i>
Flammability	Flammable Aerosol: Category 1.
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Relative Vapor Density	<i>No Data Available</i>
Density	0.95 g/ml
Relative Density	0.92 - 0.98 [Ref Std:WATER=1]
Water solubility	Complete
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	3,053 mm <sup>2</sup> /sec
Volatile Organic Compounds	10 - 12 % weight [Test Method:calculated per CARB title 2]
Percent volatile	75 - 80 % weight
VOC Less H <sub>2</sub> O & Exempt Solvents	265 - 295 g/l [Test Method:calculated per CARB title 2]
Molecular weight	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
--------------------------	-----------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

Sparks and/or flames

### 10.5. Incompatible materials

Strong oxidizing agents

Strong acids

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May cause additional health effects (see below).

#### Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Health Effects:

Single exposure may cause target organ effects:

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Mineral Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Mineral Oil	Ingestion	Rat	LD50 > 5,000 mg/kg
Isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
Sorbitan Oleate	Dermal		LD50 estimated to be > 5,000 mg/kg
Sorbitan Oleate	Ingestion	Rat	LD50 > 39,800 mg/kg
Ethanolamine	Inhalation-Vapor	official classification	LC50 estimated to be 10 - 20 mg/l
Ethanolamine	Dermal	Rabbit	LD50 2,504 mg/kg
Ethanolamine	Ingestion	Rat	LD50 1,089 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Mineral Oil	Rabbit	No significant irritation
Isobutane	Professional judgement	No significant irritation
Ethanolamine	Rabbit	Corrosive

#### Serious Eye Damage/Irritation

Name	Species	Value
Mineral Oil	Rabbit	Mild irritant
Isobutane	Professional judgement	No significant irritation
Ethanolamine	Rabbit	Corrosive

#### Skin Sensitization

Name	Species	Value
Mineral Oil	Guinea pig	Not classified
Ethanolamine	Guinea pig	Not classified

#### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Germ Cell Mutagenicity

Name	Route	Value
Mineral Oil	In Vitro	Not mutagenic
Isobutane	In Vitro	Not mutagenic
Ethanolamine	In Vitro	Not mutagenic

Ethanolamine	In vivo	Not mutagenic
--------------	---------	---------------

**Carcinogenicity**

Name	Route	Species	Value
Mineral Oil	Dermal	Mouse	Not carcinogenic
Mineral Oil	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Mineral Oil	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral Oil	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Ethanolamine	Dermal	Not classified for development	Rat	NOAEL 225 mg/kg/day	during organogenesis
Ethanolamine	Ingestion	Not classified for development	Rat	NOAEL 450 mg/kg/day	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
Ethanolamine	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Mineral Oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
Mineral Oil	Ingestion	liver	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Mineral Oil	Ingestion	immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
Ethanolamine	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	liver	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.0102 mg/l	28 days

Ethanolamine	Inhalation	heart	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	immune system	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	nervous system	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	eyes	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
Ethanolamine	Ingestion	hematopoietic system	Not classified	Rat	NOAEL Not available	
Ethanolamine	Ingestion	liver	Not classified	Rat	NOAEL Not available	
Ethanolamine	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL Not available	
Ethanolamine	Ingestion	respiratory system	Not classified	Rat	NOAEL Not available	

**Aspiration Hazard**

Name	Value
Mineral Oil	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Facility must be capable of handling aerosol cans.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

EPCRA 311/312 Hazard Classifications:

**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

**Health Hazards**

Specific target organ toxicity (single or repeated exposure)

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

This product complies with the New Zealand Hazardous Substances and New Organisms Act (1996).

**15.4. International Regulations**

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information****NFPA Hazard Classification**

**Health:** 2 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None  
**Aerosol Storage Code:** 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	10-2819-0	<b>Version Number:</b>	27.01
<b>Issue Date:</b>	12/10/25	<b>Supersedes Date:</b>	05/28/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable

for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**

